

APPENDIX B

DEPARTMENT OF DEFENSE (DOD) INTERMODAL CONTAINER STANDARDS

A. PURPOSE

To provide uniform standards for all intermodal containers owned and International Standards Organization (ISO) configured tactical shelters owned and operated by the DOD. Containers leased or contracted for use by the DOD may be excluded on a case-by-case basis as determined by mission requirements.

B. POLICY

1. All containers procured by the DOD will conform to American National Standards Institute (ANSI) and ISO standards.
2. All ISO configured tactical shelters developed or procured for the DOD intended for movement in the Defense Transportation System (DTS) or in international trade will conform to ANSI/ISO standards within mission requirements.
3. All designs for strategic and tactical transportation assets (i.e., aircraft, ships, truck, trailers) developed or procured for the DOD will consider interface with intermodal container systems of the DTS.
4. All container handling equipment procured by the DOD will adhere to ANSI/ISO standards.
5. All tactical equipment designs and procurement will consider and conform to ANSI/ISO standards within mission requirements.
6. To the maximum extent possible, procurement of ISO-configured tactical shelters will be selected from the Joint Committee on Tactical Shelters Brochure, Department of Defense Standard Family of Tactical Shelters available at (<http://www.sbccom.army.mil/hooah/pubs/jocotas.pdf>).

C. DOD STANDARDS

1. Standard transportation containers for the DOD are the:
 - a. 8' wide x 8' high x 20' long ANSI/ISO steel frame construction container.
 - b. 8' wide x 8'6" high x 20' long ANSI/ISO steel frame construction container.
 - c. 8' wide x 8'6" high x 40' long ANSI/ISO steel frame construction container.
2. The 20-foot container is designated as primary size for containerized munitions shipments. Twenty- and 40-foot ISO containers are standard for sustainment and unit equipment.
3. The capability of the user to handle and transport containers will be the overriding factor when determining container size.

D. INDUSTRY STANDARDS

1. Maximum allowable gross weight for 20' ISO containers of all types including flatracks, high-cube containers, and platform units moving in the DTS and/or international trade is 44,800 lbs (20 Long Tons).
2. Maximum allowable gross weight for 40' ISO containers of all types including flatracks, high-cube containers, and platform units moving in the DTS and/or international trade is 67,200 lbs (30 Long Tons).